

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
37278	- Channel Lighted Buoy 8A						Remove from list.
							* 3/01
CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
340 6965	Sand Shoal Inlet Lighted Whistle Buoy A	37 17 48 N 75 41 54 W	Mo (A) W		5	Red and white stripes.	
						*	3/01
700	Cape Lookout Slough West Lighted Buoy W	34 33 49 N 76 32 47 W	Mo (A) W		6	Red and white stripes.	
						*	3/01
730 29490	Bogue Inlet Entrance Lighted Whistle Buoy BI		Mo (A) W		6	Red and white stripes.	
						*	3/01
790 29650	New River Inlet Lighted Whistle Buoy NR	34 31 03 N 77 19 50 W	Mo (A) W		6	Red and white stripes.	
						*	3/01
795 29970	New Topsail Inlet Lighted Whistle Buoy NT		Mo (A) W		6	Red and white stripes.	
						*	3/01
805 30260	Carolina Beach Inlet Entrance Lighted Whistle Buoy CB		Mo (A) W		5	Red and white stripes.	
						*	3/01
Frying Pan Shoals							
820	- Slue Approach Lighted Whistle Buoy SA	33 42 37 N 77 51 05 W	Mo (A) W		6	Red and white stripes.	
						*	3/01
Delaware River (Main Channel)							
Bellevue Range							
3080	- FRONT LIGHT	39 44 06 N 75 30 18 W	Q G	36		On tower.	Visible on range line only. Lighted throughout 24 hours.
						*	3/01
3085	- REAR LIGHT 1,085 yards, 216° from front light.		F G	90		On tower.	Visible on range line only. Lighted throughout 24 hours.
	*			*		*	3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4380	- Buoy 4						Remove from list.
							* 3/01
4423	- Buoy 18						Remove from list.
							* 3/01
*Delete Heading and Note: *Indian River Bay Channel <i>*Positions of buoys frequently shifted with changing conditions.</i> <i>Buoys maintained from May 1 to Nov. 15.</i>							
4430	- Junction Buoy IR					Red and green bands; nun.	Maintained from May 1 to Nov. 15.
	*						* 3/01
*4433	- Buoy 18					Red nun.	Maintained from May 1 to Nov. 15.
							3/01
4435	- Lighted Buoy 19A		FIG 4s		4	Green.	Maintained from May 1 to Nov. 15.
							* 3/01
*Delete Heading: *White Horse Park Marina							
4947.4	- Buoy 4						Remove from list.
							* 3/01
Sand Shoal Inlet <i>Positions of buoys frequently shifted with changing conditions.</i>							
6965 340	- Lighted Whistle Buoy A	37 17 48 N 75 41 54 W	Mo (A) W		5	Red and white stripes.	
						*	3/01
12933	PLUMTREE BAR WRECK LIGHT WR2	37 07 14 N 76 16 36 W	Q R	15	4	NW on pile.	
						*	3/01
16360	- LIGHT 5		FIG 2.5s	15	4	SG on black skeleton tower on white house.	
						*	3/01
*21352	Erasmus Property Dolphin Light A		FI Y 4s		3	NY on dolphin.	Private aid.
							3/01
29395	FORT MACON REACH RANGE FRONT LIGHT	34 42 44 N 76 40 40 W	Q W	32		On pile platform.	Visible on range line only. Lighted throughout 24 hours.
		*		*		*	* 3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*29397	FORT MACON REACH RANGE FRONT PASSING LIGHT		Q W	30		On same structure as Fort Macon Reach Range Front Light.	3/01
29400	FORT MACON REACH RANGE REAR LIGHT 225 yards, 340° from front light.		Iso W 6s	45		On pile platform.	Visible on range line only. Lighted throughout 24 hours.
				*		*	* 3/01
*29403	FORT MACON REACH RANGE REAR PASSING LIGHT		FI W 4s	45		On same structure as Fort Macon Reach Range Rear Light.	Located on east end of platform. 3/01
NEUSE RIVER TO MYRTLE GROVE SOUND (Chart 11541)							
Bogue Inlet							
<i>Due to frequently changing conditions, positions of aids are not listed.</i>							
29490 730	- Entrance Lighted Whistle Buoy BI		Mo (A) W		6	Red and white stripes.	
						*	3/01
*29565.5	- Buoy 17A					Green can.	3/01
NEW RIVER (Chart 11542)							
New River Inlet							
<i>Due to frequently changing conditions, positions of aids are not listed.</i>							
29650 790	- Lighted Whistle Buoy NR	34 31 03 N 77 19 50 W	Mo (A) W		6	Red and white stripes.	
						*	3/01
NEUSE RIVER TO MYRTLE GROVE SOUND (Chart 11541)							
New Topsail Inlet							
<i>Due to frequently changing conditions, positions of aids are not listed.</i>							
29970	- Lighted Whistle Buoy NT		Mo (A) W		6	Red and white stripes.	
						*	3/01
Carolina Beach Inlet							
<i>Due to frequently changing conditions, positions of aids are not listed.</i>							
30260 805	- Entrance Lighted Whistle Buoy CB		Mo (A) W		5	Red and white stripes.	
						*	3/01
35475	- LIGHT 118	39 30 43 N 74 18 18 W	FI R 2.5s	15	6	TR-TY on pile.	
					*		3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
1350 21755	LONGBOAT PASS APPROACH LIGHT LP	27 26 05 N 82 42 07 W	Mo (A) W	16	6	MR on pile.	
		*			*		3/01
1875	- RANGE A FRONT LIGHT	33 11 34 N 79 10 05 W	Q W (Day) Q W (Night)	15 14		KRW on skeleton tower on piles.	Visible 2° each side of range line.
			*	*			* 3/01
2750.5	- MIDDLE DIKE OBSTRUCTION LIGHT	32 50 01 N 79 56 02 W	FI W 4s	21	4	NW on skeleton tower worded DANGER UNDERWATER DIKE.	
		*					3/01
Amelia River							
7045 37925	- Lighted Buoy 2	30 42 12 N 81 27 54 W	FI R 2.5s		3	Red with yellow triangle.	
		*					3/01
Canaveral Harbor							
9685.5	- Entrance Channel Lighted Buoy 14A	28 24 37 N 80 36 12 W	FI R 4s		3	Red.	
		*					3/01
9710	- Entrance Channel Lighted Buoy 20	28 24 42 N 80 37 18 W	FI R 4s		3	Red.	
		*					3/01
*21456.01	- Daybeacon 11					SG on pile.	Private aid.
							3/01
*21456.02	- Daybeacon 12					TR on pile.	Private aid.
							3/01
21610	- Channel Buoy 5					Green can.	
	*					*	3/01
Longboat Pass							
21755 1350	- APPROACH LIGHT LP	27 26 05 N 82 42 07 W	Mo (A) W	16	6	MR on pile.	
		*			*		3/01
25585.5	- Bouy 3	27 46 43 N 82 47 16 W				Green can.	
		*					3/01
33725.5	- Buoy 24B					Red nun.	
	*					*	3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Little River - Winyah Bay							
34100	- LIGHT 96	33 17 54 N 79 17 12 W	FI R 2.5s	16	3	TR-TY on pile.	
						*	3/01
ST. SIMONS SOUND - TOLOMATO RIVER (Chart 11489)							
St. Simons to Fernandina Beach							
Amelia River							
37925 7045	- Lighted Buoy 2	30 42 12 N 81 27 54 W	FI R 2.5s		3	Red with yellow triangle.	
		*					3/01
Community Harbor							
50530	- Daybeacon 1	25 01 00 N 80 01 05 W				SG on pile.	Private aid.
		*					3/01
Sand Key							
61360	- Daybeacon 1	27 47 40 N 82 46 07 W				SG-SY on pile.	
		*					3/01
CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
24020	UPPER RED LIGHT BEND OUTBOUND RANGE REAR LIGHT 215 yards, 180° from front light.		Iso G 6s	40		KRW on skeleton tower on piles. On same structure as Lower Red Light Bend Inbound Range Front Light.	Visible 2° each side of range line.
							*
							3/01
*27927.3	- LIGHT 1		FI G 2.5s	7		SG on pile.	Private aid.
							3/01
31970	- Daybeacon 59A	30 18 54 N 87 30 57 W				SG-SY on pile.	Ra ref.
		*					*
							3/01
CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12160	- LIGHT 3	45 37 55 N 121 06 41 W	FI G 6s	21	4	SG on concrete pillars.	Higher intensity beam up and down channel.
		*					3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2000							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
12210	- Daybeacon 20	45 38 53 N 120 57 58 W				TR on concrete pier.	
		*					3/01
13505	Lower Monumental Lighted Buoy 3	46 33 52 N 118 31 54 W	FI G 4s		4	Green.	
		*					3/01

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
 Denotes a new entry when preceding the station number.